

3 BY PLANKS

Industrial Mat

Features & Specifications

This durable, long lasting product provides a barrier to heavy equipment and abrasive traffic.



APPLICATIONS:

- Protects
- bridge decks
 - transport trailers
 - buildings and structures from heavy equipment and abrasive traffic

SPECIFICATIONS:

Width: 30.48cm / 12 in.
Length: 1.52 or 3.04m / 5 or 10 ft
Thickness: 7.62cm / 3 in.

PATHWAY

MATS

www.pathwaymats.com

PATHWAY MATS INC.

Head Office

Nisku, Alberta, Canada
Tel: 780 955-8786
Fax: 780 955-8746
Toll Free: 1 866 955-8786

Regional Sales Office

Calgary, Alberta, Canada
Tel: 403 265-2005
Fax: 403 271-6311
Customer Service: 1 866 955-8786

Manufacture Process:	Recycled rubber tires are granulated and compressed in a mould at a high pressure to form the moulded product.
Absorption Characteristics:	Resists most liquids including water, petroleum products and insects.
Temperature Impact:	No adverse physical effect; stiffness will increase in colder temperatures.
Abrasion Tolerance:	Resists abrasive traffic over a long time period.
Rigidity:	Two options are available. The re-enforced format adds strength to the structure which will retain some flexibility. Alternatively, the rigid option enhances stiffness and load distribution capabilities.
Installation:	3 BY PLANKS are designed to be installed on solid surfaces or over short spans. For best results, install mats on a semi smooth surface. Improper installation or usage may result in damage or reduced performance of the product.
Traffic Types:	Light to heavy equipment
Safety Features:	<ul style="list-style-type: none">- Low slippage surface- Low tripping hazard- Low puncture hazard- Resists snow and ice build up- Resists fire- Low static electricity build up or discharge
Handling Options:	Forklift, hoisting equipment, labourers.