

MINI MATS

Industrial Mat

Features & Specifications

This innovative product provides a longer term, cost effective solution for blocking trailers, drilling rigs, service rigs and other equipment.



APPLICATIONS:

- Provide a base for trailers, skids and other equipment in unstable ground or blocking under equipment for levelling purposes.

SPECIFICATIONS:

Width: 35.5 cm / 14 in.

Length: 71.2 cm / 28 in.

Thickness: 10.16 cm / 4 in.

Weight: 24.9 kgs / 55 lbs - wet or dry

PATHWAY

MATS

www.pathwaymats.com

PATHWAY MATS INC.

Head Office

Nisku, Alberta, Canada

Tel: 780 955-8786

Fax: 780 955-8746

Toll Free: 1 866 955-8786

Regional Sales Office

Calgary, Alberta, Canada

Tel: 403 265-2005

Fax: 403 271-6311

Customer Service: 1 866 955-8786

Manufacture Process:	Recycled rubber tires are granulated and compressed in a mould at a high pressure to form the moulded product.
Absorption Characteristics:	Resists most liquids including water, petroleum products and insects.
Temperature Impact:	No adverse physical effect; stiffness will increase in colder temperatures.
Abrasion Tolerance:	Resists abrasive traffic over a long time period.
Rigidity:	Equipped with a patented, torsion system to increase rigidity and load distribution capabilities. This also provides a deflection memory enabling the mat to be re-straightened.
Installation:	MINI MATS are designed to be installed on a solid to soft conditions. Multiple layers of mats may be required in some circumstances. For best results, install mats on a semi smooth surface. Improper installation or usage may result in damage or reduced performance of the product.
Traffic Types:	Heavy equipment, heavy loads.
Safety Features:	<ul style="list-style-type: none">- Low slippage surface- Low tripping hazard- Low puncture hazard- Resists snow and ice build up- Resists fire- Low static electricity build up or discharge
Handling Options:	Forklift, hoisting equipment, labourers.